



## Mettler Toledo FiveGo Portable Conductivity Meter

The Mettler Toledo FiveGo Conductivity meter is ideally suited for applications in the laboratory, outdoors or at-line. An intuitive, portable design provides high quality measurements with the simple click of a button. IP67 waterproof protection and a robust body allow for reliable measurements, even in harsh conditions.



### Features

- Robust, IP67 waterproof ABS housing.
- Large, well-structured 3.1" LCD display for easy viewing.
- One point calibration with three predefined standards.
- Features Automatic and manual endpoint recording, Acoustic endpoint signal, Visual endpoint signal.
- Intuitive button arrangement and simple menu for easy operation.
- Withstands wet and demanding environments.
- LTW 7-pin sensor inputs.
- Ideal for mobile applications in the laboratory, at-line, or outdoors.

### Specifications

Short description	Handheld meter for measuring conductivity, salinity, and TDS
Measuring range	0.00 $\mu$ S/cm to 200.0 mS/cm
Cond. accuracy	+/- 0.5%
Temperature range °C	0.0 ... 100.0
Temperature resolution °C	0.1
Temperature accuracy °C	$\pm$ 0.5
Temperature compensation	0.00 %/°C ... 10.0 %/°C
TDS range	0.0 mg/L ... 200.0 g/L
Calibration	1 point
Calibration standards	84 $\mu$ S/cm, 1413 $\mu$ S/cm, 12.88mS/cm
Free disk space	200 datasets
Display	LCD
Power supply	4 AAA batteries 1.5 V
Operating environment	0 ... 40 °C; 5 ... 85 % rel. humidity (not cond.)

